

# 1000 Series

Economy Folded Maintenance Free Respirator With or Without Comfort Exhalation Valve

## Superior Filter Media

Electrostatic charged filter media with a low breathing resistance

Effectively reducing heat and CO2 build up resulting in higher worker productivity and comfort.

## SABS Quality Mark

Manufactured under SABS Mark scheme

If you cannot see the mark on the product, it is because it does not have a SABS mark scheme permit!

Don't be fooled by products claiming to be SABS "Approved" only products with the SABS Mark on are authorised and approved to do so.

## Made in South Africa

- Designed To Suit Local Conditions
- Made by South Africans
- No Continuous Price Increases Due To Exchange Rate Fluctuations

## Usage:

Base Metal Manufacture  
 Brick Manufacture  
 Laboratories  
 Powdered Additives  
 Pharmaceutical  
 Powdered Chemicals  
 Sawmills  
 Food Industry  
 Textile industry  
 Craftwork  
 Iron and steel industry  
 Mining  
 Underground civil engineering  
 Woodworking  
 Welding work

## Quality

All respirators are **manufactured in South Africa** accordance with international standards and quality approvals.

GreenLine is ISO9001 accredited by TUV Rhineland in Germany

## Metal Nose Clip

Punched and Rounded Metal Nose Clip  
 No wires to punch through and injure users

## Foldable

Mask folds flat for easy storage and can be kept in your pocket when not in use.

## Comfort Valve

To exhaust exhaled air.  
 Effectively get workers to wear masks in hot areas.  
 Resulting in higher worker productivity and comfort

## Application:

Respirators can provide lower level protection against solid and liquid aerosols and smoke containing the following materials such as:  
 Calcium carbonate / China clay / Cement / Cellulose / Sulphur / Cotton / Flour / Carbon / Ferrous metals / Hardwood / Glass fibres / Plastic / Vegetable oils / Mineral oils / Quartz / Copper / Aluminium / Bacteria / Fungi and mycobacterium tuberculosis (T.B.)

An FFP1 has an Assigned Protection Factor (APF) of 4, FFP2 has an APF of 10 and an FFP3 has an APF of 20. Selection of the most appropriate respirator depends on the contaminant and Occupational Exposure Level (OEL) and guidance should always be sought.



1100



1200



1201